

LUMNZ Contractor Series



Ideally suited to residential or commercial applications where quality is required at a competitive price point.

Offering high lumen output with all aluminum cast casing to IP44. Matched with a quality driver on a +300mm quick connect cable. Large AC terminals, captive screws and connector between light and driver makes installation quick and easy.

Flush lens option offers wide spread of light while reducing glare. For better heat dissipation and longer LED & Driver life the driver is separated from luminaire. A quality driver with large AC terminals makes installation easy while providing great dimming and long life.



Features:

- IC-F rated
- All Aluminum Construction
- 120 Degree Beam Angle
- Dimmable
- Large Terminals 4mm ID
- Captive AC Terminal Screws
- 300mm Long Quick connect cable between light and driver
- Replaces 100W incandescent in a downlight

Technical Data

Total Wattage	11 Watt	
Color	Warm White - 3000K	Daylight - 5000K
Lumen	820Lumen	850 Lumen
Beam Angle	120 Degree	
Color Rendition (CRI)	>80	
Cutout	Min 86mm	Max 104mm
Outer Trim Size	108mm	
Height	36mm	
Approx. Lamp Life	>50000 Hours	
Ordering		
DL100-W3D	White Trim – Warm White light	Dimmable
DL100-W5D	White Trim -Daylight light	Dimmable
DL100-S3D	Silver Trim – Warm White light	Dimmable
DL100-S5D	Silver Trim -Daylight light	Dimmable

3-year Warranty